



553945

(43) International Publication Date  
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number  
WO 2005/008821 A2(51) International Patent Classification<sup>7</sup>: H01M 8/04(21) International Application Number:  
PCT/JP2004/010279

(22) International Filing Date: 13 July 2004 (13.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-277654 22 July 2003 (22.07.2003) JP(71) Applicant (for all designated States except US): NISSAN  
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-  
gawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).


(72) Inventor; and

(75) Inventor/Applicant (for US only): KAMIHARA, Tet-  
suya [JP/JP].(74) Agents: MIYOSHI, Hidekazu et al.; 9th Floor, Tora-  
nomon Daiichi Building, 2-3, Toranomom 1-chome, Mi-  
nato-ku, Tokyo 1050001 (JP).(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,  
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished  
upon receipt of that reportFor two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: FUEL CELL SYSTEM



(57) Abstract: An aspect of the present invention provides a fuel cell system that includes a fuel cell stack (1) configured to provide electric power or electric current, a cooling unit (3, 4) configured to cool the fuel cell stack (1) by flowing a coolant through a coolant passage (2) provided in the fuel cell stack (1), an inlet temperature detecting unit (5) configured to detect the temperature of the coolant at the inlet of the fuel cell stack (1), and a control unit (21) configured to control the electric power or electric current extracted from the fuel cell stack (1) in accordance with the coolant temperature detected by the inlet temperature detecting unit (5).